

## IDEAL TEMPORARY FLOORING FOR DOMESHELTER™ FABRIC STRUCTURES

- ✓ RELOCATABLE
- ✓ SUPER STRONG, EASY TO INSTALL
- ✓ HEAVY DUTY PORTABLE FLOORING



<b>Dimensions</b>	45.7 cm x 45.7cm x 5.1cm panel design
<b>Weight</b>	3.084 kg
<b>Material</b>	100% Recycled material 100% Polypropylene
<b>Color</b>	Black / Custom colors available
<b>UV Stability</b>	Good
<b>Connection System (high-strength nylon)</b>	Center locks connect 4 panels Edge locks connect perimeter panels
<b>Load Capacity</b>	392,000 kilograms per square meter
<b>Point Load Capacity</b>	3800 kPa @ 72° F
<b>Dynamic Friction</b>	Dry – 0.56 Wet – 0.44
<b>Chemical Resistance</b>	Passes ASTM tests D543-06 and D1308
<b>Flame Spread (CAN/ULC S102.2-07)</b>	Flame Spread – 50 Smoke Developed – 550
<b>Warranty</b>	5 year limited



### AVAILABLE FROM DOMESHELTER AUSTRALIA

#### STRONG

Supports over 3800kPa (557 psi),

#### PORTABLE

Engineered modular pieces quickly installed and removed

#### EASY

Quickly fits together and locks securely

Talk to a DomeShelter™ Consultant about your shelter and flooring needs